

6AG25225EH004AB0

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 6ag25225eh004ab0 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|--|
| Product ID | 6AG2522-5EH00-4AB0 |
| AL Field | N |
| Compliance | Produkt zgodny z RoHS od: 02.07.2015 |
| Configurable Product | False |
| Country of Origin | DE |
| ECCN | EAR99H |
| ETIM 7 | EC001419 |
| Group Classification Key | R151 |
| List of Characteristics | A&DSE/SIP ADD |
| Packaging Size | CM |
| Product Description | SIPLUS S7-1500 DQ 16x110VDC ST TX rail based on 6ES7522-5EH00-0AB0 with conformal coating, -40...+70 °C, OT4 with ST1/2 (+85 °C for 10 minutes), digital output module, 0.5 A; 16 channels in groups of 1, 0.5 A per group; substitute value; observe derating |
| Product Code | 4C04 |
| REACH | Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7 |
| Unit of Measure | ST |
| Customs Tariff Code | 85389091 |
| EAN | 4047618070601.0 |
| eClass 6 | 27-24-22-04 |
| eClass 7.1 | 27-24-22-04 |
| eClass 8 | 27-24-22-04 |
| eClass Version 9 | 27-24-22-04 |
| eClass Version 9.1 | 27-24-22-04 |
| Quantity in Package | 1 |
| Packaging Length | 15,30 |
| Packaging Width | 14,90 |
| Packaging Height | 4,30 |
| Comparative Metals Coefficient | 02.07.2015 |
| UPC | 804766352928.0 |
| Weight | 344 kg |

Description

SIPLUS S7-1500 DQ 16x110VDC ST TX RAIL -40 ... +70°C TX with 85°C for 10 min with conformal coating based on 6ES7522-5EH00-0AB0 . DQ 16x24 "... 48VUC/125VDC/ 0.5A; 16" channels in groups of 1, 0.5 A "per group; substitute value;" Observe derating