

### 6AG25261BH001AB0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6ag25261bh001ab0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Product ID</b>	6AG2526-1BH00-1AB0
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 02.07.2015
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>ECCN</b>	EAR99H
<b>ETIM 7</b>	EC001419
<b>Group Classification Key</b>	R151
<b>List of Characteristics</b>	A&DSE/SIP ADD
<b>Packaging Size</b>	CM
<b>Product Description</b>	SIPLUS S7-1500 F-DI 16x24VDC HF T1 rail based on 6ES7526-1BH00-0AB0 with conformal coating, -30...+60 °C, OT1 with ST1/2 (+70 °C für 10 minutes), F digital input module, 35 mm overall width; up to PL E (IS013849-1)/ SIL 3 (IEC 61508)
<b>Product Code</b>	4C04
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
<b>Unit of Measure</b>	ST
<b>Customs Tariff Code</b>	85389091
<b>EAN</b>	4047618071103.0
<b>eClass 6</b>	27-24-22-04
<b>eClass 7.1</b>	27-24-22-04
<b>eClass 8</b>	27-24-22-04
<b>eClass Version 9</b>	27-24-22-04
<b>eClass Version 9.1</b>	27-24-22-04
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	6,50
<b>Packaging Width</b>	9,20
<b>Packaging Height</b>	3,80
<b>Comparative Metals Coefficient</b>	02.07.2015
<b>UPC</b>	804766786976.0
<b>Weight</b>	350 kg

## Description

The SIPLUS S7-1500 F-DI 16x24VDC HF T1 digital input module, based on 6ES7526-1BH00-0AB0, features a conformal coating and operates within a temperature range of -30 to +60 °C, with a short-term tolerance of up to +70 °C for 10 minutes. It has an overall width of 35 mm and supports up to PL E (IS013849-1)/ SIL 3 (IEC 61508). This product is RoHS compliant since 02.07.2015 and is manufactured in Germany. The weight is 350 g, and the packaging dimensions are 6.50 x 9.20 x 3.80 cm.