

6AG25262BF001AB0

Industrial automation components

Manufacturer	Siemens
Catalog number	6ag25262bf001ab0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Product ID	6AG2526-2BF00-1AB0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 02.07.2015
Configurable Product	False
Country of Origin	DE
ECCN	EAR99H
ETIM 7	EC001419
Group Classification Key	R151
List of Characteristics	A&DSE/SIP ADD
Packaging Size	CM
Product Description	SIPLUS S7-1500 F-DQ 8x24VDC 2A T1 rail based on 6ES7526-2BF00-0AB0 with conformal coating, -30...+60 °C, OT1 with ST1/2 (+70 °C für 10 minutes), F digital output module, 35 mm overall width; up to PL e (ISO 13849-1)/ SIL3 (IEC 61508)
Product Code	4C04
REACH	Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
Unit of Measure	ST
Customs Tariff Code	85389091
EAN	4047618071011.0
eClass 6	27-24-22-04
eClass 7.1	27-24-22-04
eClass 8	27-24-22-04
eClass Version 9	27-24-22-04
eClass Version 9.1	27-24-22-04
Quantity in Package	1
Packaging Length	6,50
Packaging Width	9,20
Packaging Height	3,80
Comparative Metals Coefficient	02.07.2015
UPC	804766784859.0
Weight	388 kg

Description

The SIPLUS S7-1500 F-DQ 8x24VDC 2A T1 is a digital output module based on 6ES7526-2BF00-0AB0, designed for DIN rail mounting. It features 8 digital outputs with a voltage of 24VDC and a maximum current of 2A. The product is equipped with a conformal coating, ensuring reliability in temperatures ranging from -30 to +60 °C, with short-term operation at +70 °C for up to 10 minutes. It complies with PL e (ISO 13849-1) and SIL3 (IEC 61508) standards.