

### 6AV2124-1DC01-0AX0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6av2124-1dc01-0ax0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	1.47 kgs
Product ID	6AV2124-1DC01-0AX0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 31.01.2011
Configurable Product	False
Country of Origin	DE
ECCN	EAR99H
eClass 6	27-24-23-02
eClass 7.1	27-24-23-02
eClass 8	27-24-23-02
eClass Version 9	27-33-02-01
eClass Version 9.1	27-33-02-01
ETIM 7	EC001412
Group Classification Key	R141
List of Characteristics	ST80.1N
Packaging Length	22,20
Packaging Width	16,90
Packaging Height	6,90
Packaging Size	CM
Product Description	SIMATIC KP400 COMFORT PANEL, PANORAMICZNY WYŚWIETLACZ TFT 4", 16 MILIONÓW KOLORÓW, 8 PRZYCISKÓW FUNKCYJNYCH I KLAWIATURA ALFANUMERYCZNA, INTERFEJSY PROFIBUS/MPI, PROFINET/ETHERNET, USB; WINDOWS CE 6.0, WBUDOWANA PAMIĘĆ 4 MB, KONFIGURACJA ZA POMOCĄ TIA POR
Comparative Metals Coefficient	31.01.2011
REACH	Lead CAS-Nr. 7439-92-1; Silicic acid, lead salt lblREACHCasNo4420; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
Unit of Measure	ST
Customs Tariff Code	85371098
EAN	4025515078982.0
Quantity in Package	1
Product Code	3403
UPC	40892686067.0

## Description

The Siemens 6AV2124-1DC01-0AX0 is a SIMATIC HMI KP400 Comfort Panel designed for industrial automation applications. This device features a 4.3-inch widescreen TFT display capable of displaying 16 million colors, providing clear and vibrant visuals for operator interfaces. It offers multiple communication interfaces, including PROFINET, MPI, and PROFIBUS DP, ensuring seamless integration into various industrial networks. The panel is equipped with 4 MB of configuration memory and operates on Windows CE 6.0, allowing for efficient and reliable performance. Configurable using WinCC Comfort V11, it supports a range of industrial protocols such as PROFINET, PROFIBUS, and MPI, facilitating versatile connectivity options. The device is housed in a compact enclosure measuring 152 x 188 x 49 mm and weighs approximately 0.8 kg, making it suitable for space-constrained environments. With its robust design and comprehensive feature set, the 6AV2124-1DC01-0AX0 is an ideal choice for enhancing human-machine interaction in industrial settings.