

### 6AV2125-2AE13-0AX0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6av2125-2ae13-0ax0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.31 kgs
<b>Product ID</b>	6AV2125-2AE13-0AX0
<b>AL Field</b>	N
<b>Customs Tariff Code</b>	85369010
<b>Compliance</b>	Produkt zgodny z RoHS od: 29.06.2015
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>EAN</b>	4047623405344.0
<b>ECCN</b>	EAR99H
<b>eClass 6</b>	27-24-92-03
<b>eClass 7.1</b>	27-24-92-03
<b>eClass 8</b>	27-24-92-03
<b>eClass Version 9</b>	27-33-02-92
<b>eClass Version 9.1</b>	27-33-02-92
<b>ETIM 7</b>	EC002584
<b>Group Classification Key</b>	R141
<b>List of Characteristics</b>	ST80.1F
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	24,30
<b>Packaging Width</b>	15,90
<b>Packaging Height</b>	8,10
<b>Packaging Size</b>	CM
<b>Product Description</b>	SIMATIC HMI connection box Standard for Mobile Panels, wall mounting, PROFINET and PROFIsafe, connection of safety relay, terminal detection, integrated switch
<b>Product Code</b>	4A66
<b>Comparative Metals Coefficient</b>	29.06.2015
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7; Silicic acid, lead salt lblREACHCasNo4420
<b>Unit of Measure</b>	ST
<b>UPC</b>	804766158056.0

## Description

6AV2125-2AE13-0AX0 | Siemens, 6AV2125 Series, HMI Connection Box, 96 mA, Plastic (Enclosure), For Mobile Panels | Brand / Manufacturer: Siemens | type of accessories: HMI Connection Box | series: 6AV2125 | for use with: Mobile Panels | length: 230 mm | width: 76 mm | height: 145 mm | current rating: 96 mA | rated voltage: 24 V dc (Rated) | minimum operating temperature: 0 °C | maximum working temperature: +55 °C | Material: Plastic (Enclosure)