

### 6AV66461BC150NA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6av66461bc150na0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Product ID</b>	6AV6646-1BC15-0NA0
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 15.02.2018
<b>Configurable Product</b>	False
<b>Country of Origin</b>	Germany
<b>ECCN</b>	5A992
<b>ETIM 7</b>	EC001414
<b>Group Classification Key</b>	R141
<b>List of Characteristics</b>	ST80.1L
<b>Packaging Size</b>	CM
<b>Product Code</b>	4B45
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Silicic acid, lead salt lblREACHCasNo4420; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
<b>Unit of Measure</b>	ST
<b>Quantity in Package</b>	1
<b>Customs Tariff Code</b>	84719000
<b>EAN</b>	4047623410089
<b>eClass 6</b>	27-24-23-01
<b>eClass 7.1</b>	27-24-23-01
<b>eClass 8</b>	27-24-23-01
<b>eClass Version 9</b>	19-20-01-03
<b>eClass Version 9.1</b>	19-20-01-03
<b>Packaging Length</b>	46,80
<b>Packaging Width</b>	30,60
<b>Packaging Height</b>	19,70
<b>Comparative Metals Coefficient</b>	15.02.2018
<b>Weight</b>	7261 kg
<b>Product Description</b>	SIMATIC ITC1500 V3 PRO, Industrial Thin Client, 15" widescreen TFT display, capacitive touch sensor Supported protocols: RDP, VNC, Smart Server, HTML5, etc., neutral design, prepared for support arm without expansion elements
<b>Article Number</b>	6AV66461BC150NA0
<b>Product Family</b>	Ordering Data Overview
<b>Product Group</b>	4B45
<b>Catalog ID</b>	ST80.1L

<b>Net Weight</b>	16.008 lb
<b>Packaging Dimensions</b>	20.079 x 25.984 x 8.661
<b>Package Size Unit of Measure</b>	Inch
<b>Quantity Unit</b>	1 Piece
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85371098

## Description

The SIMATIC ITC1500 V3 PRO is an industrial thin client featuring a 15-inch widescreen TFT display and a capacitive touch sensor. This product is RoHS compliant as of February 15, 2018, and is not configurable. It supports protocols such as RDP, VNC, Smart Server, and HTML5. The design is neutral and prepared for support arm installation without expansion elements. Packaging dimensions are 46.80 x 30.60 x 19.70 cm, with a weight of 7261 g.