

### 6AV66461BC221NA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6av66461bc221na0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Product ID	6AV6646-1BC22-1NA0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 15.02.2018
Configurable Product	False
Country of Origin	Germany
ECCN	5A992
ETIM 7	EC001414
Group Classification Key	R141
List of Characteristics	ST80.1L
Packaging Size	CM
Product Code	4B45
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; Silicic acid, lead salt lblREACHCasNo4420; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
Unit of Measure	ST
Customs Tariff Code	84719000
eClass 6	27-24-23-01
eClass 7.1	27-24-23-01
eClass 8	27-24-23-01
eClass Version 9	19-20-01-03
eClass Version 9.1	19-20-01-03
Quantity in Package	1
Packaging Length	62,00
Packaging Width	40,00
Packaging Height	21,00
Comparative Metals Coefficient	15.02.2018
Weight	9760 kg
Product Description	SIMATIC ITC2200 V3 PRO, Industrial Thin Client, 22" widescreen TFT display, capacitive touch sensor, Supported protocols: RDP, VNC, SMARTSERVER, HTML5, etc., neutral design, prepared for support arm without expansion elements
EAN	4047623410027
Package Size Unit of Measure	Inch
Quantity Unit	1 Piece
Article Number	6AV66461BC221NA0
Product Family	Ordering Data Overview

<b>Product Group</b>	4B45
<b>Catalog ID</b>	ST80.1L
<b>Net Weight</b>	21.517 lb
<b>Packaging Dimensions</b>	20.079 x 25.984 x 8.661
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85371098

## Description

The SIMATIC ITC2200 V3 PRO is an industrial thin client featuring a 22-inch widescreen TFT display and a capacitive touch sensor. This product supports protocols such as RDP, VNC, SMARTSERVER, and HTML5, and boasts a neutral design prepared for support arm installation without expansion elements. Compliant with RoHS since 15.02.2018, the product is not configurable. It has a weight of 9760 g, with packaging dimensions of 62.00 x 40.00 x 21.00 cm.