

6ES7212-1HE40-0XB0

Industrial automation components

Manufacturer	Siemens
Catalog number	6es7212-1he40-0xb0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.15 kgs
Product ID	6ES7212-1HE40-0XB0
AL Field	N
Customs Tariff Code	85371091
Compliance	Produkt zgodny z RoHS od: 12.12.2013
Configurable Product	False
Country of Origin	CN
EAN	4047623402718.0
ECCN	EAR99H
eClass 6	27-24-22-07
eClass 7.1	27-24-22-07
eClass 8	27-24-22-07
eClass Version 9	27-24-22-07
eClass Version 9.1	27-24-22-07
ETIM 7	EC000236
Group Classification Key	R132
List of Characteristics	ST72
Quantity in Package	1
Packaging Length	10,70
Packaging Width	10,10
Packaging Height	8,50
Packaging Size	CM
Product Description	SIMATIC S7-1200, CPU 1212C, compact CPU, DC/DC/relay, onboard I/O: 8 DI 24 V DC; 6 DO relay 2 A; 2 AI 0-10 V DC, power supply: DC 20.4-28.8 V DC, program/data memory 100 KB
Product Code	4509
Comparative Metals Coefficient	12.12.2013
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
Unit of Measure	ST
UPC	887621769031.0

Description

6ES7212-1HE40-0XB0 | Siemens, CPU Module, 24 V dc, 75 KB (RAM), 400 mA, 12 A, 2.3 μ s for SIMATIC S7-1200 Series, Ethernet/PROFINET/UDP | Brand / Manufacturer: Siemens | height: 107 | width: 104 | depth: 88 | mass: 0.35 | product type: CPU Module | supply voltage: 24 V dc | program capacity: 75 KB (RAM) | power consumption: 400 mA | inrush current: 12 A | CPU processing time: 2.3 μ s | for use with: SIMATIC S7-1200 Series | number of digital inputs: 8 | number of digital outputs: 6 | interface type: EtherNet;PROFINET;UDP | a programming language: FBD;LAD;SCL | power loss: 9 W | encoder power supply: 24 V dc