

6ES7215-1AG40-0XB0

Industrial automation components

Manufacturer	Siemens
Catalog number	6es7215-1ag40-0xb0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.08 kgs
Product ID	6ES7215-1AG40-0XB0
AL Field	N
Customs Tariff Code	85371091
Compliance	Produkt zgodny z RoHS od: 12.12.2013
Configurable Product	False
Country of Origin	CN
EAN	4047623402756.0
ECCN	9N9999
eClass 6	27-24-22-07
eClass 7.1	27-24-22-07
eClass 8	27-24-22-07
eClass Version 9	27-24-22-07
eClass Version 9.1	27-24-22-07
ETIM 7	EC000236
Group Classification Key	R132
List of Characteristics	ST72
Quantity in Package	1
Packaging Length	14,00
Packaging Width	11,10
Packaging Height	8,50
Packaging Size	CM
Product Description	SIMATIC S7-1200, CPU 1215C, compact CPU, DC/DC/DC, 2 PROFINET ports, onboard I/O: 14 DI 24 V DC; 10 DO 24 V DC; 0.5 A; 2 AI 0-10 V DC, 2 AO 0-20 mA DC, power supply: DC 20.4-28.8 V DC, program/data memory 200 KB
Product Code	4509
Comparative Metals Coefficient	12.12.2013
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
Unit of Measure	ST
UPC	887621769086.0

Description

6ES7215-1AG40-0XB0 | Siemens CPU Module, 20.4 to 28.8 V dc, 24 V dc with LAD, FBD, SCL | Brand / Manufacturer: Siemens | mass: 0.4 | product type: CPU Module | supply voltage: 20.4 to 28.8 V dc;24 V dc | program capacity: 125 kB | power consumption: 500 mA @ 24 V dc | inrush current: 12 A @ 28.8 V dc | CPU processing time: 0.085 μ s (Bit Operation) | for use with: Simatic S7-1200 | number of digital inputs: 14 | number of digital outputs: 10 | interface type: Profinet | a programming language: LAD;FBD;SCL | power loss: 12 W | encoder power supply: 24 V