

6ES7215-1HG40-0XB0

Industrial automation components

Manufacturer	Siemens
Catalog number	6es7215-1hg40-0xb0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.19 kgs
Packaging Width	11,10
Packaging Height	8,30
Packaging Size	CM
Product Description	SIMATIC S7-1200, CPU 1215C, compact CPU, DC/DC/relay, 2 PROFINET ports, onboard I/O: 14 DI 24 V DC; 10 DO relay 2 A, 2 AI 0-10 V DC, 2 AO 0-20 mA DC, power supply: DC 20.4-28.8 V DC, program/data memory 200 KB
Product Code	4509
Comparative Metals Coefficient	12.12.2013
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
Unit of Measure	ST
UPC	887621769093.0
Quantity in Package	1
Packaging Length	13,80
Product ID	6ES7215-1HG40-0XB0
AL Field	N
Customs Tariff Code	85371091
Compliance	Produkt zgodny z RoHS od: 12.12.2013
Configurable Product	False
Country of Origin	CN
EAN	4047623402763.0
ECCN	EAR99H
eClass 6	27-24-22-07
eClass 7.1	27-24-22-07
eClass 8	27-24-22-07
eClass Version 9	27-24-22-07
eClass Version 9.1	27-24-22-07
ETIM 7	EC000236
Group Classification Key	R132
List of Characteristics	ST72

Description

6ES7-215-1HG40-0XB0 | Siemens, CPU Module, 24 V ac, Capacity 125 KB (Program), 125 KB (Data) | Brand / Manufacturer: Siemens | height: 138 | width: 116 | depth: 86 | mass: 0.47 | product type: CPU Module | supply voltage: 24 V ac | program capacity: 125 KB (Program);125 KB (Data) | power consumption: 500 mA | inrush current: 12 A | CPU processing time: 0.08 μ s (Bit Operations);1.7 μ s (Word Operations);2.3 μ s (Floating Point Arithmetic) | number of digital inputs: 14 | number of digital outputs: 10 | interface type: PROFINET Ports;Ethernet | a programming language: LAD;FBD;SCL | power loss: 12 W | encoder power supply: 24 V