

### 6ES7313-6CG04-0AB0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6es7313-6cg04-0ab0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	0.22 kgs
Product ID	6ES7313-6CG04-0AB0
Notes	Wycofanie produktu od: 01.10.2023
AL Field	N
Customs Tariff Code	85371091
Compliance	Produkt zgodny z RoHS od: 20.05.2011
Configurable Product	False
Country of Origin	DE
EAN	4025515079071.0
ECCN	EAR99H
eClass 6	27-24-22-07
eClass 7.1	27-24-22-07
eClass 8	27-24-22-07
eClass Version 9	27-24-22-07
eClass Version 9.1	27-24-22-07
ETIM 7	EC000236
Group Classification Key	R132
List of Characteristics	ST73
Quantity in Package	1
Packaging Length	15,50
Packaging Width	13,10
Packaging Height	9,10
Packaging Size	CM
Product Description	SIMATIC S7-300, JEDNOSTKA CENTRALNA KOMPAKTOWA CPU 313C-2 DP, INTERFEJSY: MPI I DP, WBUDOWANE: 16 DI/16 DO, 3 SZYBKIE LICZNIKI (30 KHZ), 128 KB PAMIĘCI WORK, WYMAGANA KARTA MMC I 1 LISTWA PRZYŁĄCZENIOWA 40PIN
Product Code	4302
Comparative Metals Coefficient	20.05.2011
REACH	Lead CAS-Nr. 7439-92-1; Silicic acid, lead salt lblREACHCasNo4420; lblREACHCode0236 lblREACHCasNo0236; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
Unit of Measure	ST
UPC	40892788587.0

## Description

6ES7313-6CG04-0AB0 | Siemens 24 V dc, Simatic S7-300, RS485 | Brand / Manufacturer: Siemens | mass: 0.5 | product type: Central Processing Unit | supply voltage: 24 V dc | program capacity: 128 kB | power consumption: 800 mA | inrush current: 5 A (Typ.) | CPU processing time: 0.07 | for use with: Simatic S7-300 | number of digital inputs: 16 | number of digital outputs: 16 | interface type: RS485