

6ES7314-6CH04-0AB0

Industrial automation components

Manufacturer	Siemens
Catalog number	6es7314-6ch04-0ab0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.33 kgs
Product ID	6ES7314-6CH04-0AB0
Notes	Wycofanie produktu od: 01.10.2023
AL Field	N
Customs Tariff Code	85371091
Compliance	Produkt zgodny z RoHS od: 13.09.2011
Configurable Product	False
Country of Origin	DE
EAN	4025515079101.0
ECCN	EAR99H
eClass 6	27-24-22-07
eClass 7.1	27-24-22-07
eClass 8	27-24-22-07
eClass Version 9	27-24-22-07
eClass Version 9.1	27-24-22-07
ETIM 7	EC000236
Group Classification Key	R132
List of Characteristics	ST73
Quantity in Package	1
Packaging Length	15,40
Packaging Width	13,40
Packaging Height	12,90
Packaging Size	CM
Product Description	SIMATIC S7-300, JEDNOSTKA CENTRALNA KOMPAKTOWA CPU 314C-2 DP, INTERFEJSY: MPI I DP, WBUDOWANE: 24 WEJŚCIA/16 WYJŚĆ BINARNYCH, 4 WEJŚCIA/2 WYJŚCIA ANALOGOWE, 1 PT100, 4 SZYBKIE LICZNIKI (60 KHZ), 192 KB PAMIĘCI WORK, WYMAGANA KARTA MMC I 2 LISTWY PRZYŁĄCZE
Product Code	4302
Comparative Metals Coefficient	13.09.2011
REACH	Lead CAS-Nr. 7439-92-1; Silicic acid, lead salt lblREACHCasNo4420; lblREACHCode0236 lblREACHCasNo0236; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7; Perfluorobutane sulfonic acid (PFBS) and its salts lblREACHCasNo0211
Unit of Measure	ST
UPC	40892788600.0

Description

6ES7314-6CH04-0AB0 | Siemens CPU Module, 24 Vdc with LAD, FBD, SCL, STL, Graph, HiGraph | Brand / Manufacturer: Siemens | mass: 0.73 | product type: CPU Module | supply voltage: 24 V dc | program capacity: 192 kB | power consumption: 880 mA | inrush current: 5 A | CPU processing time: 0.06 μ s (Bit Operation) | for use with: Simatic S7-300 | number of digital inputs: 24 | number of digital outputs: 16 | interface type: PROFIBUS DP;MPI | a programming language: LAD;FBD;SCL;STL;Graph;HiGraph | power loss: 13 W