

6ES7318-3FL01-0AB0

Industrial automation components

Manufacturer	Siemens
Catalog number	6es7318-3fl01-0ab0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.12 kgs
Product ID	6ES7318-3FL01-0AB0
Notes	Wycofanie produktu od: 01.10.2023
AL Field	N
Customs Tariff Code	85371091
Compliance	Produkt zgodny z RoHS od: 06.08.2010
Configurable Product	False
Country of Origin	DE
EAN	4025515077886.0
ECCN	EAR99H
eClass 6	27-24-22-07
eClass 7.1	27-24-22-07
eClass 8	27-24-22-07
eClass Version 9	27-24-22-07
eClass Version 9.1	27-24-22-07
ETIM 7	EC000236
Group Classification Key	R152
List of Characteristics	ST73
Quantity in Package	1
Packaging Length	18,10
Packaging Width	16,70
Packaging Height	15,50
Packaging Size	CM
Product Description	SIMATIC S7-300, jednostka centralna Fail-Safe CPU 319F-3 PN/DP, interfejsy: MPI/DP, DP i Ethernet/PROFINET (SWITCH 2 X RJ45), 2.5 MB pamięci work, funkcje Fail-Safe wymagają pakietu S7 DISTRIBUTED SAFETY w wersji V5.4 SP3 lub nowszej, wymagana karta MMC
Product Code	4A85
Comparative Metals Coefficient	06.08.2010
REACH	Dodecachloropentacyclo[12.2.1.16,9.02,13.05,10]octadeca-7,15-diene ("Dechlorane Plus™") covering any of its individual anti- and syn-isomers or any combination thereof lblREACHCasNo0007
Unit of Measure	ST
UPC	40892692990.0

Description

6ES7318-3FL01-0AB0 | Siemens CPU Module, 24 Vdc with LAD, FBD, SCL, STL, Graph, HiGraph, CFC | Brand / Manufacturer: Siemens | height: 150 | width: 350 | depth: 120 | mass: 1.4 | product type: CPU Module | supply voltage: 24 V dc | program capacity: 2.5 MB | power consumption: 1250 mA | inrush current: 4 A | CPU processing time: 0.004 μ s (Bit Operation) | for use with: Simatic S7-300 | interface type: RS-485 | a programming language: LAD;FBD;SCL;STL;Graph;HiGraph;CFC | power loss: 14 W