

### 6ES7323-1BH01-0AA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6es7323-1bh01-0aa0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.20 kgs
<b>Product ID</b>	6ES7323-1BH01-0AA0
<b>Notes</b>	Wycofanie produktu od: 01.10.2023
<b>AL Field</b>	N
<b>Customs Tariff Code</b>	85389091
<b>Compliance</b>	Produkt zgodny z RoHS od: 31.03.2008
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>EAN</b>	4025515065289.0
<b>ECCN</b>	N
<b>eClass 6</b>	27-24-22-04
<b>eClass 7.1</b>	27-24-22-04
<b>eClass 8</b>	27-24-22-04
<b>eClass Version 9</b>	27-24-22-04
<b>eClass Version 9.1</b>	27-24-22-04
<b>ETIM 7</b>	EC001419
<b>Group Classification Key</b>	R151
<b>List of Characteristics</b>	ST73
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	15,10
<b>Packaging Width</b>	12,80
<b>Packaging Height</b>	5,00
<b>Packaging Size</b>	CM
<b>Product Description</b>	SIMATIC S7-300, moduł wejść/wyjść binarnych SM 323, 8 wejść/8 wyjść, 24V DC/0.5A, prąd grupy 2A, izolacja optyczna, wymagana listwa przyłączeniowa 20 PIN
<b>Product Code</b>	2288
<b>Comparative Metals Coefficient</b>	31.03.2008
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Perfluorobutane sulfonic acid (PFBS) and its salts lblREACHCasNo0211
<b>Unit of Measure</b>	ST
<b>UPC</b>	662643173758.0

## Description

6ES7-323-1BH01-0AA0 | Siemens SIMATIC S7-300 Series Digital Input Module, 40 mA Input, 0.5 A Output, 24 V dc, 40 x 125 x 120 mm | Brand / Manufacturer: Siemens | product type: Digital Input Module | series: SIMATIC S7-300 | number of contributions: 8 | type of contribution: Digital | module type: Digital Input Module | input current: 40 mA (Load Voltage);40 mA (Backplane) | output current: 0.5 A (for Signal 1 Rated value);5 mA (for Signal 1 Permissible Range, min);0.6 A (for Signal 1 Permissible Range, Max);5 mA (for Signal 1 Minimum Load Current);0.5 mA (for Signal 0 Residual Current, Max) | supply voltage: 24 V dc | switch-on time: 1.2 ms (Minimum);4.8 ms (Maximum) | off time: 1.2 ms (Minimum);4.8 ms (Maximum) | Size: 40 x 125 x 120 mm