

### 6ES7331-7PF11-0AB0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6es7331-7pf11-0ab0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.32 kgs
<b>Product ID</b>	6ES7331-7PF11-0AB0
<b>Notes</b>	Wycofanie produktu od: 01.10.2023
<b>AL Field</b>	N
<b>Customs Tariff Code</b>	85389091
<b>Compliance</b>	Produkt zgodny z RoHS od: 31.03.2008
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>EAN</b>	4025515072027.0
<b>ECCN</b>	9N9999
<b>eClass 6</b>	27-24-22-01
<b>eClass 7.1</b>	27-24-22-01
<b>eClass 8</b>	27-24-22-01
<b>eClass Version 9</b>	27-24-22-01
<b>eClass Version 9.1</b>	27-24-22-01
<b>ETIM 7</b>	EC001420
<b>Group Classification Key</b>	R151
<b>List of Characteristics</b>	ST73
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	15,00
<b>Packaging Width</b>	13,10
<b>Packaging Height</b>	5,00
<b>Packaging Size</b>	CM
<b>Product Description</b>	SIMATIC S7-300, moduł wejść analogowych SM 331, 8 wejść, pomiar termopar typu B, E, J, K, L, N, R, S, T TXK/TXK(L) rozdzielczość 16 BITów, czas odświeżania 50 MS, izolacja optyczna, wymagana listwa przyłączeniowa 40 PIN
<b>Product Code</b>	2288
<b>Comparative Metals Coefficient</b>	31.03.2008
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; lblREACHCode0236 lblREACHCasNo0236; Perfluorobutane sulfonic acid (PFBS) and its salts lblREACHCasNo0211
<b>Unit of Measure</b>	ST
<b>UPC</b>	662643177930.0

## Description

6ES7-331-7PF11-0AB0 | Siemens SIMATIC S7-300 Series Analogue Input Module, 240 mA (Load Voltage);100 mA (Backplane), 75 V dc/24 V dc, 40 x 125 x 120 mm | Brand / Manufacturer: Siemens | product type: Analogue Input Module | series: SIMATIC S7-300 | number of contributions: 8 | type of contribution: Analogue | module type: Analogue Input Module | input current: 240 mA (Load Voltage);100 mA (Backplane) | supply voltage: 75 V dc;24 V dc (Rated Value) | Size: 40 x 125 x 120 mm