

### 6ES7416-5HS06-0AB0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6es7416-5hs06-0ab0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	1.31 kgs
Product ID	6ES7416-5HS06-0AB0
AL Field	N
Customs Tariff Code	85389091
Compliance	Produkt zgodny z RoHS od: 05.04.2012
Configurable Product	False
Country of Origin	DE
EAN	4019169234597.0
ECCN	9N9999
eClass 6	27-24-22-07
eClass 7.1	27-24-22-07
eClass 8	27-24-22-07
eClass Version 9	27-24-22-07
eClass Version 9.1	27-24-22-07
ETIM 7	EC000236
Group Classification Key	R338
List of Characteristics	ST74
Quantity in Package	1
Packaging Length	29,50
Packaging Width	23,30
Packaging Height	6,30
Packaging Size	CM
Product Description	SIMATIC S7-400H PROFINET, JEDNOSTKA CENTRALNA DLA SYSTEMÓW REDUNDANTNYCH ORAZ REDUNDANTNYCH/FAIL-SAFE CPU 416-5H, INTERFEJSY: 1 X MPI/DP, 1 X DP, 1 X PN (SWITCH 2 X 45) , 2 X DOŁĄCZANE MODUŁY SYNCHRONIZACJI; 16 MB PAMIĘCI WORK (6 MB PROGRAM, 10 MB DANE)
Product Code	4040
Comparative Metals Coefficient	05.04.2012
REACH	Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7; Lead monoxide (lead oxide) lblREACHCasNo7368
Unit of Measure	ST
UPC	40892932379.0

## Description

6ES7416-5HS06-0AB0 | Siemens CPU Module, 24 Vdc with LAD, FBD, SCL, STL, Graph, HiGraph, CFC | Brand / Manufacturer: Siemens | product type: CPU Module | supply voltage: 24 V dc | program capacity: 16 MB | power consumption: 1.6 A | CPU processing time: 12.5 ns (Bit Operation) | for use with: Simatic S7-400H;S7-400H;S7-400F/H | number of digital inputs: 131 | number of digital outputs: 131 | interface type: MPI/DP;Profinet;RS-485 | a programming language: LAD;FBD;SCL;STL;Graph;HiGraph;CFC | power loss: 7.5 W