

### 6ES7512-1CK01-0AB0

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 6es7512-1ck01-0ab0               |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                |   |
|--------------------------------|---|
| Weight                         | 1.36 kgs  |
| Product ID                     | 6ES7512-1CK01-0AB0  |
| AL Field                       | N   |
| Customs Tariff Code            | 85371091  |
| Compliance                     | Produkt zgodny z RoHS od: 29.03.2018  |
| Configurable Product           | False   |
| Country of Origin              | CN  |
| EAN                            | 4047623408642.0   |
| ECCN                           | EAR99H  |
| eClass 6                       | 27-24-22-07   |
| eClass 7.1                     | 27-24-22-07   |
| eClass 8                       | 27-24-22-07   |
| eClass Version 9               | 27-24-22-07   |
| eClass Version 9.1             | 27-24-22-07   |
| ETIM 7                         | EC000236  |
| Group Classification Key       | R132  |
| List of Characteristics        | ST73  |
| Quantity in Package            | 1   |
| Packaging Length               | 23,80   |
| Packaging Width                | 18,90   |
| Packaging Height               | 17,00   |
| Packaging Size                 | CM  |
| Product Code                   | 4500  |
| Comparative Metals Coefficient | 29.03.2018  |
| REACH                          | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide)<br>lblREACHCasNo7368; Silicic acid, lead salt<br>lblREACHCasNo4420 |
| Unit of Measure                | ST  |
| UPC                            | 804766662577.0  |

## Description

SIMATIC S7-1500 Compact CPU CPU 1512C-1 PN, central processing unit with working memory 250 KB for program and 1 MB for data, 32 digital inputs, 32 digital outputs, 5 analog inputs, 2 analog outputs, 6 high speed counters, 4 high speed outputs for PTO/PWM/frequency output 1. interface: PROFINET IRT with 2 port switch, 48 NS bit-performance, incl. front connector push-in, SIMATIC memory card necessary