

### 6FC5303-0AF22-0AA1

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6fc5303-0af22-0aa1
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.65 kgs
<b>eClass 6</b>	27-24-21-03
<b>eClass 7.1</b>	27-24-21-03
<b>eClass 8</b>	27-24-21-03
<b>eClass Version 9</b>	27-24-21-03
<b>eClass Version 9.1</b>	27-24-21-03
<b>ETIM 7</b>	EC001422
<b>List of Characteristics</b>	NC62
<b>ECCN</b>	9N9999
<b>Packaging Length</b>	0,00
<b>Packaging Width</b>	0,00
<b>Packaging Height</b>	0,00
<b>Product Description</b>	SINUMERIK MACHINE CONTROL PANEL MCP 483C PN PROFINET / INDUSTRIAL ETHERNET, WIDTH 19", MECHANICAL KEYS, 22 MM EMERGENCY STOP
<b>Product Code</b>	X0HM
<b>Comparative Metals Coefficient</b>	15.07.2015
<b>Unit of Measure</b>	ST
<b>Product ID</b>	6FC5303-0AF22-0AA1
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 15.07.2015
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Dodecachloropentacyclo[12.2.1.1 6,9.02,13.05,10]octadeca-7,15-diene ("Dechlorane Plus" <sup>™</sup> ) covering any of its individual anti- and syn-isomers or any combination thereof lblREACHCasNo0007; Cadmium sulphide lblREACHCasNo4310
<b>Customs Tariff Code</b>	85371098
<b>Quantity in Package</b>	1
<b>UPC</b>	40892744125.0
<b>Group Classification Key</b>	R211

## Description

The Siemens 6FC5303-0AF22-0AA1 is a SINUMERIK Machine Control Panel (MCP 483C PN) designed for industrial automation applications. This panel features a 19-inch width, mechanical keys, and a 22 mm emergency stop button, ensuring reliable operation in demanding environments. It supports PROFINET and Industrial Ethernet interfaces, facilitating seamless integration into modern automation systems. The panel operates on a 24 V DC input voltage, making it suitable for various industrial settings. With dimensions of 483 x 155 x 106 mm and a weight of approximately 2 kg, it offers a compact and robust solution for machine control needs.