6FX5002-5DG10-1DA0

Industrial automation components

Add to quote

Ask about this product



Manufacturer	Siemens
Catalog number	6fx5002-5dg10-1da0
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Product Type	Pre-assembled power cable
Connector Type	SPEED-CONNECT connector size 1
Cable Configuration	4x 1.5 mm² cores and 2x 1.5 mm² cores
Cable Sheath Material	PVC
Cable Sheath Color	Orange (RAL 2003)
Operating Temperature Range (Stationary)	-20°C to 80°C
Operating Temperature Range (Moving)	0°C to 60°C
Flame Resistance Standard	EN 60332-1-1 to 1-3
Oil Resistance Standard	EN 60811-2-1
UL Standard	UL 758
CSA Standard	CSA-C22.2-N.210.2-M90

Description

6FX5002-5DG10-1DA0 - pre-assembled power cable, Siemens. SPEED-CONNECT connector size 1, cable for SINAMICS S120 AC drives; four 1.5 mm² cores and two 1.5 mm² cores. PVC sheath in orange (RAL 2003).

Temperature range: -20°C to 80°C stationary, 0°C to 60°C moving. Flame resistance: EN 60332-1-1 to 1-3. Oil resistance: EN 60811-2-1.

Automation Trader
960 Capability Green
Luton, Bedfordshire LU1 3PE
VAT ID: PL6463009354
REGON: 527345886
DUNS: 427734105
BDO: 000726360

Phone
+44 7418 359 399

Email
info@automationtrader.com

Generated on demand. The PDF file is not stored on the server.

Approved to UL 758 and CSA-C22.2-N.210.2-M90. Maximum outer diameter 10.8 mm, minimum bending radius 27 mm.

Automation Trader
960 Capability Green
Luton, Bedfordshire LU1 3PE

VAT ID: PL6463009354
REGON: 527345886
DUNS: 427734105
BDO: 000726360

Phone
+44 7418 359 399

Email
info@automationtrader.com

Generated on demand. The PDF file is not stored on the server.