

### 6FX50022DC102AA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6fx50022dc102aa0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	7027 kg
<b>Customs Tariff Code</b>	85444290
<b>eClass 6</b>	27-06-18-01
<b>eClass 7.1</b>	27-06-18-01
<b>eClass 8</b>	27-06-18-01
<b>eClass Version 9</b>	27-06-18-01
<b>eClass Version 9.1</b>	27-06-18-01
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	0,00
<b>Packaging Width</b>	0,00
<b>Packaging Height</b>	0,00
<b>Product Code</b>	9300
<b>Comparative Metals Coefficient</b>	01.07.2006
<b>UPC</b>	662643237115.0
<b>Product ID</b>	6FX5002-2DC10-2AA0
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.07.2006
<b>Configurable Product</b>	False
<b>Country of Origin</b>	SK
<b>ECCN</b>	N
<b>ETIM 7</b>	EC003249
<b>Group Classification Key</b>	R220
<b>List of Characteristics</b>	NCZ-M
<b>Product Description</b>	PRZEWÓD SYGNAŁOWY KONFEKCJONOWANY (SINAMICS DRIVE CLIQ) WTYCZKA IP20/IP67, Z 24 V MOTION-CONNECT 500 DŁUGOŚĆ (M) = 100
<b>Unit of Measure</b>	ST

## Description

The pre-assembled signal cable (SINAMICS DRIVE CLIQ) features an IP20/IP67 connector, designed for use in automation systems. It has a length of 100 meters and operates at 24 V. The product weighs 6.94 kg and complies with RoHS standards since 01.07.2006. Its compatibility with eClass versions 6, 7.1, 8, and 9 ensures high quality and industrial standards. The product is non-configurable and originates from SK. There is 1 unit per package.