

### 6GK1588-3AA15

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6gk1588-3aa15
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Product ID</b>	6GK1588-3AA15
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.09.2006
<b>Country of Origin</b>	JP
<b>ECCN</b>	N
<b>eClass 6</b>	27-26-17-04
<b>eClass 7.1</b>	27-26-17-04
<b>eClass 8</b>	27-26-17-04
<b>eClass Version 9</b>	27-26-17-04
<b>eClass Version 9.1</b>	27-26-17-04
<b>ETIM 7</b>	EC002584
<b>Group Classification Key</b>	R322
<b>List of Characteristics</b>	IK
<b>Packaging Length</b>	1,00
<b>Packaging Width</b>	1,00
<b>Packaging Height</b>	1,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	ASIC SPC 4-2 LF for PROFIBUS DP/ FMS/ PA and FF for intrinsically safe connection 31.25 Kbit/s and max. 12 Mbit/s tray 160 units lead-free solderable design. Please note: the dimensions have changed slightly compared to 6GK1588-2AA.
<b>Comparative Metals Coefficient</b>	01.09.2006
<b>REACH</b>	Lead CAS-Nr. 7439-92-1
<b>Unit of Measure</b>	SZ
<b>EAN</b>	4019169853323.0
<b>Quantity in Package</b>	1
<b>Product Code</b>	2447
<b>UPC</b>	662643185690.0
<b>Weight</b>	528
<b>Customs Tariff Code</b>	85423990
<b>Configurable Product</b>	False