

### 6GK5206-2BD00-2AB2

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6gk5206-2bd00-2ab2
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Customs Tariff Code	85176200
EAN	4047623091578.0
eClass 6	19-17-01-06
eClass 7.1	19-17-01-06
eClass 8	19-17-01-06
eClass Version 9	19-17-01-06
eClass Version 9.1	19-17-01-06
Quantity in Package	1
Packaging Length	80,00
Packaging Width	117,00
Packaging Height	109,00
Product Code	2456
Comparative Metals Coefficient	01.01.2003
Weight	283 kg
Product ID	6GK5206-2BD00-2AB2
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.01.2003
Configurable Product	False
Country of Origin	DE
ECCN	9N9999
ETIM 7	EC000734
Group Classification Key	R320
List of Characteristics	IK
Packaging Size	MM
Product Description	SCALANCE XB206-2 managed Layer 2 IE switch 6x 10/100 Mbps RJ45 ports 2x MM F0 SC port 1x console port, diagnostics LED redundant power supply; IEC 62443-4-2 certified; temperature range 0 °C to +60 °C; DIN-rail mounting; default PROFINET.
REACH	Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
Unit of Measure	ST

## Description

SCALANCE XB206-2 managed Layer 2 IE switch 6x 10/100 Mbps RJ45 ports 2x MM F0 SC port 1x console port, diagnostics LED redundant power supply; IEC 62443-4-2 certified; temperature range 0 °C to +60 °C; DIN-rail mounting; default PROFINET.