

6GK52062GS002FC2

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 6gk52062gs002fc2 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|--------------------------------------|
| Packaging Width | 60,00 |
| Packaging Height | 147,00 |
| Comparative Metals Coefficient | 01.01.2003 |
| UPC | 804766812316.0 |
| Weight | 520 |
| Customs Tariff Code | 85176200 |
| EAN | 4047622614327.0 |
| eClass 6 | 19-17-01-06 |
| eClass 7.1 | 19-17-01-06 |
| eClass 8 | 19-17-01-06 |
| eClass Version 9 | 19-17-01-06 |
| eClass Version 9.1 | 19-17-01-06 |
| Quantity in Package | 1 |
| Packaging Length | 125,00 |
| Product ID | 6GK5206-2GS00-2FC2 |
| AL Field | N |
| Compliance | Produkt zgodny z RoHS od: 01.01.2003 |
| Configurable Product | False |
| Country of Origin | DE |
| ECCN | 9N9999 |
| ETIM 7 | EC000734 |
| Group Classification Key | R320 |
| List of Characteristics | IK |
| Packaging Size | MM |
| Product Code | 4D83 |
| REACH | Lead CAS-Nr. 7439-92-1 |
| Unit of Measure | ST |

Description

SCALANCE XC206-2SFP G EEC Manageable layer 2 IE switch; 6x 10/100/1000 Mbit/s RJ45 ports; 2x 1000 Mbit/s SFP; 1x console port; Diagnostics LED; Redundant power supply; with painted printed circuit boards; NAMUR NE21-compliant; Temp. range -40 °C to +70 °C Mounting: Standard mounting rail/S7 mounting rail/wall; Redundancy functions; Office features (RSTP, VLAN,...); PROFINET IO device; Ethernet/IP-compliant; C-PLUG slot;