

### 6GK5213-3BD00-2AB2

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6gk5213-3bd00-2ab2
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.45 kgs
<b>Customs Tariff Code</b>	85176200
<b>EAN</b>	4047622178416.0
<b>Quantity in Package</b>	1
<b>Product Code</b>	2456
<b>UPC</b>	804766163098.0
<b>Product ID</b>	6GK5213-3BD00-2AB2
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.01.2003
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>ECCN</b>	9N9999
<b>eClass 6</b>	19-17-01-06
<b>eClass 7.1</b>	19-17-01-06
<b>eClass 8</b>	19-17-01-06
<b>eClass Version 9</b>	19-17-01-06
<b>eClass Version 9.1</b>	19-17-01-06
<b>ETIM 7</b>	EC000734
<b>Group Classification Key</b>	R320
<b>List of Characteristics</b>	IK
<b>Packaging Length</b>	125,00
<b>Packaging Width</b>	120,00
<b>Packaging Height</b>	147,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	SCALANCE XB213-3 managed Layer 2 IE switch 13x 10/100 Mbit/s RJ45 ports, 3x MM F0 SC-port 1x console port, diagnostics LED, redundant power supply, IEC 62443-4-2 certified; temperature range 0 °C to +60 °C; DIN-rail mounting; default PROFINET.
<b>Comparative Metals Coefficient</b>	01.01.2003
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
<b>Unit of Measure</b>	ST