

### 6GK52244GS002FC2

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6gk52244gs002fc2
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Customs Tariff Code	85176200
eClass 6	19-17-01-06
eClass 7.1	19-17-01-06
eClass 8	19-17-01-06
eClass Version 9	19-17-01-06
eClass Version 9.1	19-17-01-06
Quantity in Package	1
Packaging Length	124,00
Packaging Width	120,00
Packaging Height	125,00
Comparative Metals Coefficient	01.01.2003
UPC	195125257979.0
Weight	520 kg
Product ID	6GK5224-4GS00-2FC2
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.01.2003
Configurable Product	False
ECCN	9N9999
ETIM 7	EC000734
Group Classification Key	R320
List of Characteristics	IK
Packaging Size	MM
Product Code	4D83
REACH	Lead CAS-Nr. 7439-92-1
Unit of Measure	ST
EAN	4047622642535
Country of Origin	Germany
Article Number	6GK52244GS002FC2
Product Family	SCALANCE XC-200EEC managed
Product Group	4D83
Catalog ID	IK
Packaging Dimensions	8.071 x 8.071 x 8.268
Package Size Unit of Measure	Inch
Quantity Unit	1 Piece
Net Weight	1.146 lb

<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85176200
<b>Operating Temperature Range</b>	-40 to +70 °C

## Description

SCALANCE XC224-4C G EEC manageable layer 2 IE Switch; Full Gigabit; 20x 10/100/1000 Mbps RJ45 ports; 4x 1000 Mbps Combo ports (either 1000 Mbps/ s SFPs or 10/100/1000 Mbps RJ45 ports can be used); 1x console port; Diagnostic LED; Redundant power supply; with painted printed circuit boards; NAMUR NE21-compliant, Temp. range -40 °C to +70 °C; Mounting: Standard Mounting Rail/S7 Profile Rail/Wall redundancy functions; office features (RSTP, VLAN,...); PROFINET IO Device; Ethernet/IP-compliant, C-PLUG shaft;