

6GK5308-2FL10-2AA3

Industrial automation components

Manufacturer	Siemens
Catalog number	6gk5308-2fl10-2aa3
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.62 kgs
Customs Tariff Code	85176200
EAN	4047622157442.0
Quantity in Package	1
Product Code	2425
UPC	887621775797.0
Configurable Product	False
Product ID	6GK5308-2FL10-2AA3
Notes	Wycofanie produktu od: 30.12.2023 The XC/XCM-300 portfolio is available as successor
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.10.2008
Country of Origin	DE
Packaging Length	123,00
ECCN	9N9999
eClass 6	19-17-01-06
eClass 7.1	19-17-01-06
eClass 8	19-17-01-06
eClass Version 9	19-17-01-06
eClass Version 9.1	19-17-01-06
ETIM 7	EC000734
Group Classification Key	R320
List of Characteristics	IK
REACH	Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
Unit of Measure	ST
Packaging Width	120,00
Packaging Height	125,00
Packaging Size	MM
Comparative Metals Coefficient	01.10.2008

Description

6GK5308-2FL10-2AA3 | Siemens, Ethernet Switch, 6GK5308 Series, 18 to 32 V dc, 0.4 A | Brand / Manufacturer: Siemens | depth: 190 | product type: Ethernet Switch | series: 6GK5308 | model: SCALANCE X308-2 | number of LAN ports: 1 (RJ-45) | data transfer rate: 10 Mbit/s;100 Mbit/s;1000 Mbit/s | current rating: 0.4 A | supply voltage: 18 to 32 V dc | power loss: 9.6 W | length: 120 mm | width: 123 mm | height: 125 mm | level of security: IP30 | type of attachment: DIN Rail Mount;Wall Mount | requirements met: EN 60079-0:2006;EN 60079-15:2005;UL 60950-1;CSA C22.2 No. 60950-1;UL 1604 and UL 2279-15;EN 61000-6-4:2007;EN 61000-6-2:2005;CE Certified | mass: 1.4 kg