

### 6GK5534-2TR00-4AR3

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 6gk5534-2tr00-4ar3               |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                |  |
|--------------------------------|--|
| Customs Tariff Code            | 85176200   |
| EAN                            | 4047622989531.0  |
| eClass 6                       | 19-17-01-06  |
| eClass 7.1                     | 19-17-01-06  |
| eClass 8                       | 19-17-01-06  |
| eClass Version 9               | 19-17-01-06  |
| eClass Version 9.1             | 19-17-01-06  |
| Packaging Length               | 305,00   |
| Packaging Width                | 449,00   |
| Packaging Height               | 130,80   |
| Product Code                   | 2425   |
| Comparative Metals Coefficient | 23.10.2009   |
| Weight                         | 3000 kg  |
| Product ID                     | 6GK5534-2TR00-4AR3   |
| AL Field                       | N  |
| Compliance                     | Produkt zgodny z RoHS od: 23.10.2009   |
| Configurable Product           | False  |
| Country of Origin              | DE   |
| ECCN                           | 9N9999   |
| ETIM 7                         | EC000734   |
| Group Classification Key       | R320   |
| List of Characteristics        | IK   |
| Packaging Size                 | MM   |
| REACH                          | Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7 |
| Unit of Measure                | ST   |
| Quantity in Package            | 1  |

## Description

SCALANCE XR526-8; managed layer 3 IE switch, 19" rack; 24x 100/1000 Mbps RJ45 port; 2x 1G/2.5G/5G/10 Gbps RJ45 port, 8x 1G/10G SFP+ port; LED diagnostics; error signaling contact; select/set button; PROFINET IO device; network management; integrated redundancy manager; office features (RSTP, VLAN, IGMP,..); CLP included in scope of supply; power supply 2x 230 V AC