

### 6GK5734-1FX00-0AA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6gk5734-1fx00-0aa0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	0.45 kgs
Customs Tariff Code	85176200
EAN	4047622148112.0
Quantity in Package	1
Product Code	2405
UPC	887621775773.0
Group Classification Key	R323
List of Characteristics	IK
Packaging Length	74,00
Packaging Width	50,00
Packaging Height	114,00
Packaging Size	MM
Comparative Metals Coefficient	01.01.2003
Product ID	6GK5734-1FX00-0AA0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.01.2003
Configurable Product	False
Country of Origin	DE
ECCN	9N9999
eClass 6	19-17-02-09
eClass 7.1	19-17-02-09
eClass 8	19-17-02-09
eClass Version 9	19-17-02-09
eClass Version 9.1	19-17-02-09
ETIM 7	EC000816
REACH	Lead CAS-Nr. 7439-92-1; Dodecachloropentacyclo[12.2.1.1 6,9.02,13.05,10]octadeca-7,15-diene ("Dechlorane Plus™") covering any of its individual anti- and syn-isomers or any combination thereof lblREACHCasNo0007
Unit of Measure	ST

## Description

6GK5734-1FX00-0AA0 | Siemens, IWLAN Dual Access Point, 24 V dc, 2.41 to 2.48 GHz (WLAN in 2.4 GHz Frequency Band)/4.9 to 5.8 GHz (WLAN in 5 GHz Frequency Band 1), 10 to 1000 Mbit/s, 127 x 26 x 147 mm | Brand / Manufacturer: Siemens | mass: 0.61 | product type: IWLAN Dual Access Point | wireless transmission technology: IWLAN | frequency classification: 2.41 to 2.48 GHz (WLAN in 2.4 GHz Frequency Band);4.9 to 5.8 GHz (WLAN in 5 GHz Frequency Band 1) | data transfer indicator: 10 to 1000 Mbit/s | number of antenna connectors: 2 | supply voltage: 24 V dc | minimum operating temperature: -20 °C | maximum working temperature: +60 °C | type of attachment: DIN Rail Mount | depth: 127 mm | width: 26 mm | height: 147 mm | level of security: IP30