

### 6GK57881GY010AA0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6gk57881gy010aa0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Customs Tariff Code	85176200
EAN	4047622611180.0
eClass 6	19-17-02-01
eClass 7.1	19-17-02-01
eClass 8	19-17-02-01
eClass Version 9	19-17-02-01
eClass Version 9.1	19-17-02-01
Quantity in Package	1
Packaging Length	30,00
Packaging Width	133,00
Packaging Height	45,00
Product Code	2407
Comparative Metals Coefficient	01.01.2003
UPC	195125068520.0
Weight	1971
Product ID	6GK5788-1GY01-0AA0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.01.2003
Configurable Product	False
Country of Origin	DE
ECCN	9N9999
ETIM 7	EC000816
Group Classification Key	R323
List of Characteristics	IK
Packaging Size	MM
REACH	Lead CAS-Nr. 7439-92-1; Dodecachloropentacyclo[12.2.1.1.1.6,9.02,13.05,10]octadeca-7,15-diene ("Dechlorane Plus™") covering any of its individual anti- and syn-isomers or any combination thereof lblREACHCasNo0007
Unit of Measure	ST
Product Family	SCALANCE W1788 M12 for indoor use
Catalog ID	IK
Packaging Dimensions	0.039 x 0.039 x 0.039
Package Size Unit of Measure	Inch
Quantity Unit	1 Piece
Voltage Rating	24 V

<b>IP Rating</b>	IP65
<b>Article Number</b>	6GK57881GY010AA0
<b>Product Group</b>	2407
<b>Net Weight</b>	4.345 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85176200

## Description

IWLAN access point, SCALANCE W1788-1 M12, 1 radio, 4 N-CON antenna port, iFeatures support via CLP, IEEE 802.11a/b/g/h/n/ac, 2.4/5 GHz, gross 1733 Mbit/s per radio, 2x M12 max. 1 Gbit/s, PoE, redundant 24 V DC, M12 A-coded IP65, -20..+70 °C, CLP slot, WPA2/802.11i/e, observe national approvals! CERT ID: RAPAC-W1-M12-E4, includes: MPCIE-R1-ABGNAC-U4 Scope of delivery: Manuals on DVD, German/English, M12 sealing caps, for operation outside of USA/Israel