

6GK7443-1EX30-0XE0

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 6gk7443-1ex30-0xe0 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|---------------------------------------|---|
| Weight | 0.28 kgs |
| Product ID | 6GK7443-1EX30-0XE0 |
| AL Field | N |
| Customs Tariff Code | 85176200 |
| Compliance | Produkt zgodny z RoHS od: 11.05.2012 |
| Configurable Product | False |
| Country of Origin | DE |
| EAN | 4019169206709.0 |
| ECCN | 9N9999 |
| eClass 6 | 27-24-22-08 |
| eClass 7.1 | 27-24-22-08 |
| eClass 8 | 27-24-22-08 |
| eClass Version 9 | 27-24-22-08 |
| eClass Version 9.1 | 27-24-22-08 |
| ETIM 7 | EC001423 |
| Group Classification Key | R322 |
| List of Characteristics | IK |
| Quantity in Package | 1 |
| Packaging Length | 129,00 |
| Packaging Width | 35,00 |
| Packaging Height | 142,00 |
| Packaging Size | MM |
| Product Description | SIMATIC NET, PROCESOR KOMUNIKACYJNY CP 443-1 UMOŻLIWIAJĄCY PODŁĄCZENIE SIMATIC S7-400 DO SIECI INDUSTRIAL ETHERNET OBSŁUGIWANE PROTOKOŁY/FUNKCJE: ISO, TCP/IP I UDP, KOMUNIKACJA S7, FUNKCJE: FETCH/WRITE, OPEN COMMUNICATION (SEND/RECV), MULTICAST, CONTROLER |
| Product Code | 2414 |
| Comparative Metals Coefficient | 11.05.2012 |
| REACH | Lead CAS-Nr. 7439-92-1; Tris(4-nonylphenyl, branched and linear) phosphite (TNPP) with greater than or equal to 0.1% w/w of 4-nonylphenol, branched and linear (4-NP) lblREACHCasNo0198 |
| Unit of Measure | ST |
| UPC | 40892953275.0 |

Description

6GK7443-1EX30-0XE0 | Siemens Communication Module, 5 V dc, 1.4 A, 10 to 100 Mbit/s, RJ45, 25 x 290 x 210 mm, 0.7 kg | Brand / Manufacturer: Siemens | product type: Communication Module | module type: Communication Module | supply voltage: 5 V dc | current rating: 1.4 A | data transfer indicator: 10 to 100 Mbit/s | interface type: RJ-45 Port | Size: 25 x 290 x 210 mm | minimum operating temperature: 0 °C | maximum working temperature: 60 °C | mass: 0.7 kg | length: 290 mm | width: 25 mm | depth: 210 mm