

### 6GK7543-1AX00-0XE0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6gk7543-1ax00-0xe0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.03 kgs
<b>Customs Tariff Code</b>	85176200
<b>EAN</b>	4019169224277.0
<b>Quantity in Package</b>	1
<b>Product Code</b>	2443
<b>UPC</b>	887621150105.0
<b>Packaging Length</b>	86,00
<b>Packaging Width</b>	54,00
<b>Packaging Height</b>	0,80
<b>Packaging Size</b>	MM
<b>Product ID</b>	6GK7543-1AX00-0XE0
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 27.02.2013
<b>Configurable Product</b>	False
<b>Country of Origin</b>	DE
<b>ECCN</b>	9N9999
<b>eClass 6</b>	27-24-22-08
<b>eClass 7.1</b>	27-24-22-08
<b>eClass 8</b>	27-24-22-08
<b>eClass Version 9</b>	27-24-22-08
<b>eClass Version 9.1</b>	27-24-22-08
<b>ETIM 7</b>	EC001423
<b>Group Classification Key</b>	R322
<b>List of Characteristics</b>	IK
<b>Product Description</b>	SIMATIC S7-1500, PROCESOR KOMUNIKACYJNY CP 1543-1 DO PODŁĄCZENIA S7-1500 DO SIECI INDUSTRIAL ETHERNET; OBSŁUGIWANE PROTOKOŁY: TCP/IP, ISO, UDP, KOMUNIKACJA S7, IP-BROADCAST/MULTICAST, FUNKCJE BEZPIECZEŃSTWA (HARDWARE- IDENTIFICATION, IP/MAC ACCESS LIST, F
<b>Comparative Metals Coefficient</b>	27.02.2013
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7
<b>Unit of Measure</b>	ST

## Description

6GK7543-1AX00-0XE0 | Siemens Communication Module for Connection of SIMATIC S7-1500 to Industrial EtherNet, 0.35 A @ 15 V, 10 to 1000 Mbit/s, Rail Mount, 35 x 142 x 129 mm, 0.35 kg | Brand / Manufacturer: Siemens | product type: Communication Module | module type: Communication Module | supply voltage: 15 V dc | current rating: 0.35 A @ 15 V | for use with: Connection of SIMATIC S7-1500 to Industrial Ethernet | data transfer indicator: 10 to 1000 Mbit/s | interface type: RJ-45 Port | type of attachment: Rail Mount | Size: 35 x 142 x 129 mm | minimum operating temperature: 0 °C | maximum working temperature: +40 °C (Vertical);+60 °C (Horizontal) | mass: 0.35 kg | length: 142 mm | width: 35 mm | depth: 129 mm