

### 6GT2801-2BA10

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6gt2801-2ba10
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	0.11 kgs
Product ID	6GT2801-2BA10
AL Field	N
Customs Tariff Code	84719000
Compliance	Produkt zgodny z RoHS od: 01.03.2003
Configurable Product	False
Country of Origin	DE
EAN	4047622417959.0
ECCN	N
eClass 6	27-28-04-01
eClass 7.1	27-28-04-01
eClass 8	27-28-04-01
eClass Version 9	27-28-04-01
eClass Version 9.1	27-28-04-01
ETIM 7	EC002998
Group Classification Key	R322
List of Characteristics	ID10.M
Quantity in Package	1
Packaging Length	106,00
Packaging Width	76,00
Packaging Height	42,00
Packaging Size	MM
Product Description	SIMATIC RF300; Reader RF340R (GEN2); RS422 interface (3964R); IP67, -25 to +70 °C, 75x 75x 41 mm with integrated antenna .
Product Code	9471
Comparative Metals Coefficient	01.03.2003
REACH	Lead CAS-Nr. 7439-92-1
Unit of Measure	ST
UPC	804766348686.0

## Description

6GT2801-2BA10 | Siemens, Reader 24 V dc, 20.4 to 28.8 V dc, 0.06, 0.25 kg | Brand / Manufacturer: Siemens | product type: Reader | module type: Reader | supply voltage: 24 V dc;20.4 to 28.8 V dc | current rating: 0.06 A | for use with: SIMATIC RF300 | data transfer indicator: 106 Kbit/s;115.2 Kbit/s | interface type: RS422 | type of attachment: Screw Mount | Size: 75 x 41 x 75 mm | minimum operating temperature: -25 °C | maximum working temperature: +70 °C | mass: 0.25 kg | length: 75 mm | width: 41 mm | depth: 75 mm