

### 6SL31114VE216EA1

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 6sl31114ve216ea1                 |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                |   |
|--------------------------------|---|
| Customs Tariff Code            | 85044086  |
| eClass 6                       | 27-02-31-01   |
| eClass 7.1                     | 27-02-31-01   |
| eClass 8                       | 27-02-31-01   |
| eClass Version 9               | 27-02-31-01   |
| eClass Version 9.1             | 27-02-31-01   |
| Quantity in Package            | 1   |
| Packaging Length               | 380,00  |
| Packaging Width                | 455,00  |
| Packaging Height               | 500,00  |
| Product Code                   | 9601  |
| Comparative Metals Coefficient | 31.05.2017  |
| UPC                            | 804766545795.0  |
| Weight                         | 18950 kg  |
| Product ID                     | 6SL3111-4VE21-6EA1  |
| AL Field                       | N   |
| Compliance                     | Produkt zgodny z RoHS od: 31.05.2017  |
| Configurable Product           | False   |
| Country of Origin              | CN  |
| ECCN                           | 3A999A  |
| ETIM 7                         | EC001857  |
| Group Classification Key       | R220  |
| List of Characteristics        | D21MC   |
| Packaging Size                 | MM  |
| REACH                          | Lead CAS-Nr. 7439-92-1; Dodecachloropentacyclo[12.2.1.1 6,9.02,13.05,10]octadeca-7,15-diene ("Dechlorane Plus™") covering any of its individual anti- and syn-isomers or any combination thereof<br>lblREACHCasNo0007 |
| Unit of Measure                | ST  |

## Description

SINAMICS S120 Combi Power Module Input: 400 V 3AC, 16 kW Output: 400 V 3AC, 24 A, 9 A, 9 A, 9 A, Design: combi External air cooling Support of the extended Safety Integrated functions