

### 6SL3130-7TE31-2AA3

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6sl3130-7te31-2aa3
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	2.29 kgs
Product ID	6SL3130-7TE31-2AA3
AL Field	N
Customs Tariff Code	85044095
Compliance	Produkt zgodny z RoHS od: 20.08.2015
Configurable Product	False
Country of Origin	DE
EAN	4025515005476.0
ECCN	9N9999
eClass 6	27-02-91-12
eClass 7.1	27-02-91-12
eClass 8	27-02-91-12
eClass Version 9	27-02-31-91
eClass Version 9.1	27-02-31-91
ETIM 7	EC002025
Group Classification Key	R220
List of Characteristics	D21MC
Quantity in Package	1
Packaging Length	0,00
Packaging Width	0,00
Packaging Height	0,00
Product Description	SINAMICS S120 ACTIVE LINE MODULE WEJŚCIE: 3AC 380-480V, 50/60HZ WYJŚCIE: DC 600V, 200A, 120KW RODZAJ OBUDOWY: BOOKSIZE CHŁODZENIE WEWNĘTRZNE DOŁĄCZONY PRZEWÓD SYGNAŁOWY DRIVE-CLIQ
Product Code	9617
Comparative Metals Coefficient	20.08.2015
Unit of Measure	ST
UPC	662643433272.0

## Description

6SL3130-7TE31-2AA3 | Siemens Line Module 3 Phase 192 A 120 kW | Brand / Manufacturer: Siemens | product type: Line Module | number of phases: 3 | current rating: 192 A | supply voltage: 380 to 480 V | power classification: 120 kW | frequency classification: 50 / 60 Hz | level of security: IP20 | minimum operating temperature: 0 °C | maximum working temperature: 40 °C | Total length: 300 mm | total width: 270 mm | total height: 380 mm | mass: 23 kg