

### 6SL3200-0AE50-0AA0

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 6sl3200-0ae50-0aa0               |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Legacy / discontinued            |

## Technical specification

|                                |                                      |
|--------------------------------|--------------------------------------|
| Weight                         | 0.69 kgs                             |
| EAN                            | 4042948674482.0                      |
| ECCN                           | EAR99H                               |
| eClass 6                       | 27-02-31-01                          |
| Product ID                     | 6SL3200-0AE50-0AA0                   |
| AL Field                       | N                                    |
| Customs Tariff Code            | 85044085                             |
| Compliance                     | Produkt zgodny z RoHS od: 05.07.2010 |
| Configurable Product           | False                                |
| Country of Origin              | CN                                   |
| eClass 7.1                     | 27-02-31-01                          |
| eClass 8                       | 27-02-31-01                          |
| eClass Version 9               | 27-02-31-01                          |
| eClass Version 9.1             | 27-02-31-01                          |
| ETIM 7                         | EC001857                             |
| Group Classification Key       | R220                                 |
| List of Characteristics        | SINAMICS V20                         |
| Quantity in Package            | 1                                    |
| Packaging Length               | 33,00                                |
| Packaging Width                | 28,50                                |
| Packaging Height               | 19,70                                |
| Packaging Size                 | CM                                   |
| Product Code                   | X052                                 |
| Comparative Metals Coefficient | 05.07.2010                           |
| Unit of Measure                | ST                                   |
| UPC                            | 804766462382.0                       |

## Description

Starter kit SINAMICS V20 Consisting of SINAMICS V20 Rated power 0.37 kW with 150% overload for 60 s. 200-240 V 1 AC -10/+10% 47-63 Hz Integrated filter C1 I/O interface: 4 DI, 2 DQ, 2 AI, 1 AQ Fieldbus: USS/MODBUS RTU With built-in BOP Degree of protection IP20/UL Open Type Size: FSAA 68x142x108 (WxHxD) Parameter loader BOP interface V20 BOP Smart Access The delivery quantity is limited to 3 units per customer.