

6SL3210-1KE11-8UF2

Industrial automation components

Manufacturer	Siemens
Catalog number	6sl3210-1ke11-8uf2
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.54 kgs
Product ID	6SL3210-1KE11-8UF2
AL Field	N
Customs Tariff Code	85044095
Compliance	Produkt zgodny z RoHS od: 01.07.2006
Configurable Product	False
Country of Origin	GB
EAN	4042948668672.0
ECCN	N
eClass 6	27-02-31-01
eClass 7.1	27-02-31-01
eClass 8	27-02-31-01
eClass Version 9	27-02-31-01
eClass Version 9.1	27-02-31-01
ETIM 7	EC001857
Group Classification Key	R220
List of Characteristics	D11.1SD
Quantity in Package	1
Packaging Length	225,00
Packaging Width	270,00
Packaging Height	85,00
Packaging Size	MM
Product Code	5673
Comparative Metals Coefficient	01.07.2006
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7; Diboron trioxide lblREACHCasNo3950
Unit of Measure	ST
UPC	804766249495.0

Description

6SL3210-1KE11-8UF2 | Siemens AC Drive, 3, 2.3 A @ L0, 1.9 A @ H0, 380 to 480 V ac, 0.55 kW @ L0, 0.37 kW @ H0 | Brand / Manufacturer: Siemens | product type: AC Drive | number of phases: 3 | current rating: 2.3 A @ L0;1.9 A @ H0 | supply voltage: 380 to 480 V ac | power classification: 0.55 kW @ L0;0.37 kW @ H0 | frequency classification: 0 to 240 Hz (Vector Control);0 to 550 Hz (V/F Control) | level of security: IP20 | minimum operating temperature: -10 | maximum working temperature: +40 | Total length: 73 mm