

6SL3210-1KE13-2AF2

Industrial automation components

Manufacturer	Siemens
Catalog number	6sl3210-1ke13-2af2
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	0.11 kgs
Product ID	6SL3210-1KE13-2AF2
AL Field	N
Customs Tariff Code	85044095
Compliance	Produkt zgodny z RoHS od: 01.07.2006
Configurable Product	False
Country of Origin	GB
EAN	4042948668764.0
ECCN	N
eClass 6	27-02-31-01
eClass 7.1	27-02-31-01
eClass 8	27-02-31-01
eClass Version 9	27-02-31-01
eClass Version 9.1	27-02-31-01
ETIM 7	EC001857
Group Classification Key	R220
List of Characteristics	D11.1SD
Quantity in Package	1
Packaging Length	225,00
Packaging Width	270,00
Packaging Height	85,00
Packaging Size	MM
Product Code	5673
Comparative Metals Coefficient	01.07.2006
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7; Diboron trioxide lblREACHCasNo3950
Unit of Measure	ST
UPC	804766249563.0

Description

6SL3210-1KE13-2AF2 | Siemens, SINAMICS G120C Series, Inverter Drive, 0.75 kW, 380 to 480 V, 3.20 A, IP20 | Brand / Manufacturer: Siemens | product type: Inverter Drive | power classification: 0.75 kW (H0);0.10 kW (L0) | supply voltage: 380 to 480 V | current rating: 3.20 A (IN);3.10 A (L0);2.20 A (H0) | output frequency: 0 to 240 Hz (Vector Control);0 to 550 Hz (V/F Control) | ambient temperature: -10 to +40 °C | filter included yes / no: No | function: Variable Frequency Flux Current Control;Vector Control | series: SINAMICS G120C | level of security: IP20 | type of attachment: Screw Mount | Power assessment in horsepower: 0.75 to 25 hp | Size: 73.0 x 173.0 x 178.0 mm | requirements met: EMC Directive 2004/108/EC, Low-Voltage Directive 2006/95/EC;UL, cUL, CE, C-Tick (RCM) | mass: 1.40 kg