

### 6SL3210-1KE13-2UP2

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 6sl3210-1ke13-2up2               |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                       |  |
|---------------------------------------|--|
| <b>Weight</b>                         | 0.50 kgs   |
| <b>Product ID</b>                     | 6SL3210-1KE13-2UP2   |
| <b>AL Field</b>                       | N  |
| <b>Customs Tariff Code</b>            | 85044085   |
| <b>Compliance</b>                     | Produkt zgodny z RoHS od: 01.07.2006   |
| <b>Configurable Product</b>           | False  |
| <b>Country of Origin</b>              | GB   |
| <b>EAN</b>                            | 4042948668801.0  |
| <b>ECCN</b>                           | N  |
| <b>eClass 6</b>                       | 27-02-31-01  |
| <b>eClass 7.1</b>                     | 27-02-31-01  |
| <b>eClass 8</b>                       | 27-02-31-01  |
| <b>eClass Version 9</b>               | 27-02-31-01  |
| <b>eClass Version 9.1</b>             | 27-02-31-01  |
| <b>ETIM 7</b>                         | EC001857   |
| <b>Group Classification Key</b>       | R220   |
| <b>List of Characteristics</b>        | D11.1SD  |
| <b>Quantity in Package</b>            | 1  |
| <b>Packaging Length</b>               | 225,00   |
| <b>Packaging Width</b>                | 270,00   |
| <b>Packaging Height</b>               | 85,00  |
| <b>Packaging Size</b>                 | MM   |
| <b>Product Description</b>            | SINAMICS G120C RATED POWER 1,1KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED<br>I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF<br>INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL<br>OPEN TYPE SIZE: FSAA 173X73X155(HXWXD) EXTERNAL 24V |
| <b>Product Code</b>                   | 5673   |
| <b>Comparative Metals Coefficient</b> | 01.07.2006   |
| <b>REACH</b>                          | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide)<br>lblREACHCasNo7368; 4,4'-isopropylidenediphenol<br>(Bisphenol A, BPA) CAS-Nr. 80-05-7; Diboron trioxide<br>lblREACHCasNo3950  |
| <b>Unit of Measure</b>                | ST   |
| <b>UPC</b>                            | 804766249594.0   |