

### 6SL3210-1KE15-8UF2

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 6sl3210-1ke15-8uf2               |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                       |   |
|---------------------------------------|---|
| <b>Weight</b>                         | 1.36 kgs  |
| <b>Product ID</b>                     | 6SL3210-1KE15-8UF2  |
| <b>AL Field</b>                       | N   |
| <b>List of Characteristics</b>        | D11.1SD   |
| <b>Packaging Length</b>               | 225,00  |
| <b>Packaging Width</b>                | 270,00  |
| <b>Packaging Height</b>               | 85,00   |
| <b>Packaging Size</b>                 | MM  |
| <b>Compliance</b>                     | Produkt zgodny z RoHS od: 01.07.2006  |
| <b>Configurable Product</b>           | False   |
| <b>Country of Origin</b>              | GB  |
| <b>ECCN</b>                           | N   |
| <b>eClass 6</b>                       | 27-02-31-01   |
| <b>eClass 7.1</b>                     | 27-02-31-01   |
| <b>eClass 8</b>                       | 27-02-31-01   |
| <b>eClass Version 9</b>               | 27-02-31-01   |
| <b>eClass Version 9.1</b>             | 27-02-31-01   |
| <b>ETIM 7</b>                         | EC001857  |
| <b>Group Classification Key</b>       | R220  |
| <b>Product Description</b>            | SINAMICS G120C RATED POWER 2,2KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSAA 173X73X178(HXWXD) EXTERNAL 24V |
| <b>Comparative Metals Coefficient</b> | 01.07.2006  |
| <b>REACH</b>                          | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7; Diboron trioxide lblREACHCasNo3950  |
| <b>Unit of Measure</b>                | ST  |
| <b>Customs Tariff Code</b>            | 85044095  |
| <b>Quantity in Package</b>            | 1   |
| <b>EAN</b>                            | 4042948668917.0   |
| <b>Product Code</b>                   | 5673  |
| <b>UPC</b>                            | 804766242243.0  |

## Description

6SL3210-1KE15-8UF2 | Siemens, SINAMICS G120C Series, Inverter Drive, 2.2 kW, 380 to 480 V ac, 7.4 A, 0 to 550 Hz (V/F Control)/0 to 240 Hz (Vector Control), 73 x 173 x 178 mm | Brand / Manufacturer: Siemens | product type: Inverter Drive | power classification: 2.2 kW | supply voltage: 380 to 480 V ac | current rating: 7.4 A | output frequency: 0 to 550 Hz (V/F Control);0 to 240 Hz (Vector Control) | ambient temperature: -10 to +40 °C | filter included yes / no: No | series: SINAMICS G120C | level of security: IP20