

6SL3210-1KE18-8UB1

Industrial automation components

Manufacturer	Siemens
Catalog number	6sl3210-1ke18-8ub1
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Weight	1.21 kgs
Quantity in Package	1
Product Code	5673
UPC	887621117375.0
Customs Tariff Code	85044085
EAN	4042948663233.0
Product ID	6SL3210-1KE18-8UB1
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.07.2006
Configurable Product	False
Country of Origin	GB
ECCN	N
eClass 6	27-02-31-01
eClass 7.1	27-02-31-01
eClass 8	27-02-31-01
eClass Version 9	27-02-31-01
eClass Version 9.1	27-02-31-01
ETIM 7	EC001857
Group Classification Key	R220
List of Characteristics	D11.1SD
Packaging Length	225,00
Packaging Width	270,00
Packaging Height	85,00
Packaging Size	MM
Comparative Metals Coefficient	01.07.2006
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7; Diboron trioxide lblREACHCasNo3950
Unit of Measure	ST

Description

6SL3210-1KE18-8UB1 | Siemens, SINAMICS G120C Series, Inverter Drive, 3.00 kW, 380 to 480 V, 9.00 A, IP20 | Brand / Manufacturer: Siemens | product type: Inverter Drive | power classification: 3.00 kW (H0);4.00 kW (L0) | supply voltage: 380 to 480 V | current rating: 9.00 A (IN);8.80 A (L0);7.30 A (H0) | output frequency: 0 to 240 Hz (Vector Control);0 to 550 Hz (V/F Control) | ambient temperature: -10 to +40 °C | filter included yes / no: No | function: Variable Frequency Flux Current Control;Vector Control | series: SINAMICS G120C | level of security: IP20 | type of attachment: Screw Mount | Power assessment in horsepower: 0.75 to 25 hp | Size: 73.0 x 196.0 x 203.0 mm | requirements met: EMC Directive 2004/108/EC, Low-Voltage Directive 2006/95/EC;UL, cUL, CE, C-Tick (RCM) | mass: 1.70 kg