

### 6SL3210-1KE18-8UP1

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6sl3210-1ke18-8up1
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	2.27 kgs
<b>Product Code</b>	5673
<b>UPC</b>	887621019174.0
<b>Customs Tariff Code</b>	85044095
<b>EAN</b>	4042948663479.0
<b>Quantity in Package</b>	1
<b>Product ID</b>	6SL3210-1KE18-8UP1
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.07.2006
<b>Configurable Product</b>	False
<b>Country of Origin</b>	GB
<b>ECCN</b>	N
<b>eClass 6</b>	27-02-31-01
<b>eClass 7.1</b>	27-02-31-01
<b>eClass 8</b>	27-02-31-01
<b>eClass Version 9</b>	27-02-31-01
<b>eClass Version 9.1</b>	27-02-31-01
<b>ETIM 7</b>	EC001857
<b>Group Classification Key</b>	R220
<b>List of Characteristics</b>	D11.1SD
<b>Packaging Length</b>	225,00
<b>Packaging Width</b>	270,00
<b>Packaging Height</b>	85,00
<b>Packaging Size</b>	MM
<b>Comparative Metals Coefficient</b>	01.07.2006
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7; Diboron trioxide lblREACHCasNo3950
<b>Unit of Measure</b>	ST
<b>Product Description</b>	SINAMICS G120C RATED POWER 4,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203(HXWXD) EXTERNAL 24V

## Description

6SL3210-1KE18-8UP1 | Siemens, SINAMICS G120C Series, Inverter Drive, 4 kW, 380 to 480 V ac, 11.4 A, 0 to 550 Hz (V/F Control)/0 to 240 Hz (Vector Control), 73 x 196 x 203 mm | Brand / Manufacturer: Siemens | height: 225 | width: 270 | depth: 85 | mass: 2.1 | product type: Inverter Drive | power classification: 4 kW | supply voltage: 380 to 480 V ac | current rating: 11.4 A | output frequency: 0 to 550 Hz (V/F Control);0 to 240 Hz (Vector Control) | ambient temperature: -10 to +40 °C | filter included yes / no: No | series: SINAMICS G120C | level of security: IP20