

### 6SL3210-1KE21-7AP1

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6sl3210-1ke21-7ap1
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	1.44 kgs
<b>Product Code</b>	5673
<b>UPC</b>	887621085599.0
<b>Packaging Size</b>	MM
<b>Customs Tariff Code</b>	85044095
<b>EAN</b>	4042948663370.0
<b>Quantity in Package</b>	1
<b>AL Field</b>	N
<b>Product ID</b>	6SL3210-1KE21-7AP1
<b>Packaging Width</b>	255,00
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.07.2006
<b>Configurable Product</b>	False
<b>Country of Origin</b>	GB
<b>ECCN</b>	N
<b>eClass 6</b>	27-02-31-01
<b>eClass 7.1</b>	27-02-31-01
<b>eClass 8</b>	27-02-31-01
<b>eClass Version 9</b>	27-02-31-01
<b>eClass Version 9.1</b>	27-02-31-01
<b>ETIM 7</b>	EC001857
<b>Group Classification Key</b>	R220
<b>List of Characteristics</b>	D11.1SD
<b>Packaging Length</b>	260,00
<b>Packaging Height</b>	125,00
<b>Comparative Metals Coefficient</b>	01.07.2006
<b>REACH</b>	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7; Diboron trioxide lblREACHCasNo3950
<b>Unit of Measure</b>	ST

## Description

6SL3210-1KE21-7AP1 | Siemens, SINAMICS G120C Series, Inverter Drive, 5.50 kW, 380 to 480 V, 17.00 A, IP20 | Brand / Manufacturer: Siemens | product type: Inverter Drive | power classification: 5.50 kW (H0);7.50 kW (L0) | supply voltage: 380 to 480 V | current rating: 17.00 A (IN);16.50 A (L0);12.50 A (H0) | output frequency: 0 to 240 Hz (Vector Control);0 to 550 Hz (V/F Control) | ambient temperature: -10 to +40 °C | filter included yes / no: No | function: Variable Frequency Flux Current Control;Vector Control | series: SINAMICS G120C | level of security: IP20 | type of attachment: Screw Mount | Power assessment in horsepower: 0.75 to 25 hp | Size: 100.0 x 196.0 x 203.0 mm | requirements met: EMC Directive 2004/108/EC, Low-Voltage Directive 2006/95/EC;UL, cUL, CE, C-Tick (RCM) | mass: 2.30 kg