

### 6SL3210-1KE23-8AF1

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6sl3210-1ke23-8af1
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	0.86 kgs
AL Field	N
Customs Tariff Code	85044095
ECCN	N
EAN	4042948663882.0
Quantity in Package	1
Packaging Size	MM
Product Code	5673
UPC	887621144036.0
Compliance	Produkt zgodny z RoHS od: 01.07.2006
Configurable Product	False
Country of Origin	GB
Product ID	6SL3210-1KE23-8AF1
eClass 6	27-02-31-01
eClass 8	27-02-31-01
eClass Version 9.1	27-02-31-01
Comparative Metals Coefficient	01.07.2006
ETIM 7	EC001857
Group Classification Key	R220
List of Characteristics	D11.1SD
eClass 7.1	27-02-31-01
eClass Version 9	27-02-31-01
Packaging Length	270,00
Packaging Width	365,00
Packaging Height	160,00
Unit of Measure	ST
REACH	Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) \b\bREACHCasNo7368; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7; Diboron trioxide \b\bREACHCasNo3950

## Description

6SL3210-1KE23-8AF1 | Siemens AC Drive, 3, 48.26 A @ L0, 45.2 A @ H0, 380 to 480 V ac, 18.5 kW @ L0, 15 kW @ H0 | Brand / Manufacturer: Siemens | height: 270 | width: 365 | depth: 160 | mass: 2.4 | product type: AC Drive | number of phases: 3 | current rating: 48.26 A @ L0;45.2 A @ H0 | supply voltage: 380 to 480 V ac | power classification: 18.5 kW @ L0;15 kW @ H0 | frequency classification: 0 to 240 Hz (Vector Control);0 to 550 Hz (V/F Control) | level of security: IP20 | minimum operating temperature: -10 | maximum working temperature: +40 | Total length: 140 mm