

### 6SL3210-1PE16-1UL1

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 6sl3210-1pe16-1ul1               |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                |   |
|--------------------------------|---|
| Weight                         | 0.82 kgs  |
| Customs Tariff Code            | 85044095  |
| Compliance                     | Produkt zgodny z RoHS od: 01.07.2006                          |
| Configurable Product           | False   |
| Country of Origin              | GB  |
| EAN                            | 4042948665992.0   |
| ECCN                           | N   |
| eClass 6                       | 27-02-31-01   |
| eClass 7.1                     | 27-02-31-01   |
| eClass 8                       | 27-02-31-01   |
| eClass Version 9               | 27-02-31-01   |
| Product Code                   | 9772  |
| Comparative Metals Coefficient | 01.07.2006  |
| REACH                          | Lead CAS-Nr. 7439-92-1; Diboron trioxide<br>lbrREACHCasNo3950 |
| Unit of Measure                | ST  |
| UPC                            | 887621778897.0  |
| Product ID                     | 6SL3210-1PE16-1UL1  |
| AL Field                       | N   |
| eClass Version 9.1             | 27-02-31-01   |
| ETIM 7                         | EC001857  |
| Group Classification Key       | R220  |
| List of Characteristics        | D11.1SD   |
| Quantity in Package            | 1   |
| Packaging Length               | 260,00  |
| Packaging Width                | 80,00   |
| Packaging Height               | 180,00  |
| Packaging Size                 | MM  |

## Description

SINAMICS Power Module PM240-2 unfiltered with integrated braking chopper 380-480 V 3 AC +10/-10% 47-63 Hz Power high overload: 1.5kW at 200% 3s, 150% 57s, 100% 240 s; Ambient temperature -10 to +50 °C; power low overload: 2.2kW at 150% 3s, 110% 57s, 100% 240 s; Ambient temperature -10 to +40 °C 196x 73x 165 (HxWxD), FSA Degree of protection IP20 without Control Unit and operating unit Released as of CU firmware version V4.6