

### 6SL3210-1PE32-5AL0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6sl3210-1pe32-5al0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	70.76 kgs
Product ID	6SL3210-1PE32-5AL0
AL Field	N
Customs Tariff Code	85044095
Compliance	Produkt zgodny z RoHS od: 01.01.2017
Product Code	9775
Comparative Metals Coefficient	01.01.2017
REACH	Lead CAS-Nr. 7439-92-1; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7; Diboron trioxide lblREACHCasNo3950; Cadmium oxide lblREACHCasNo0450
Unit of Measure	ST
UPC	804766258381.0
Configurable Product	False
Country of Origin	DE
EAN	4042948668252.0
ECCN	9N9999
eClass 6	27-02-31-01
eClass 7.1	27-02-31-01
eClass 8	27-02-31-01
eClass Version 9	27-02-31-01
eClass Version 9.1	27-02-31-01
ETIM 7	EC001857
Group Classification Key	R220
List of Characteristics	D11.1SD
Quantity in Package	1
Packaging Length	745,00
Packaging Width	469,00
Packaging Height	385,00
Packaging Size	MM

## Description

SINAMICS G120 POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 110KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 132kW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP -20 TO +40 DEG C (LO) 708 X 305 X 357 (HXWXD), FSF PROTECTION IP20 WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.7 HF8