

### 6SL3210-5BB17-5BV1

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6sl3210-5bb17-5bv1
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.41 kgs
<b>Product ID</b>	6SL3210-5BB17-5BV1
<b>AL Field</b>	N
<b>Customs Tariff Code</b>	85044095
<b>Compliance</b>	Produkt zgodny z RoHS od: 05.07.2010
<b>Configurable Product</b>	False
<b>Country of Origin</b>	CN
<b>EAN</b>	4042948669853.0
<b>ECCN</b>	N
<b>eClass 6</b>	27-02-31-01
<b>eClass 7.1</b>	27-02-31-01
<b>eClass 8</b>	27-02-31-01
<b>eClass Version 9</b>	27-02-31-01
<b>eClass Version 9.1</b>	27-02-31-01
<b>ETIM 7</b>	EC001857
<b>Group Classification Key</b>	R220
<b>List of Characteristics</b>	SINAMICS V20
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	225,00
<b>Packaging Width</b>	140,00
<b>Packaging Height</b>	180,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	SINAMICS V20 200-240V 1AC -10/+10% 47-63Hz rated power 0.75 kW with 150% overload for 60 sec. integrated filter C1 I/O: 4 DI, 2 DO, 2 AI, 1 AQ fieldbus: USS/MODBUS RTU with built-in BOP protection: IP20/ UL open size: QB 68x142x128 (WxHxD)
<b>Product Code</b>	5680
<b>Comparative Metals Coefficient</b>	05.07.2010
<b>Unit of Measure</b>	ST
<b>UPC</b>	804766253355.0