

### 6SL3210-5BB17-5UV1

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6sl3210-5bb17-5uv1
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	0.36 kgs
eClass Version 9	27-02-31-01
eClass Version 9.1	27-02-31-01
ETIM 7	EC001857
Group Classification Key	R220
List of Characteristics	SINAMICS V20
Quantity in Package	1
Packaging Length	225,00
Packaging Width	140,00
Packaging Height	180,00
Packaging Size	MM
Product Description	SINAMICS V20 200-240V 1AC -10/+10% 47-63Hz rated power 0.75 kW with 150% overload for 60 sec. unfiltered I/O: 4 DI, 2 DO, 2 AI, 1 AQ fieldbus: USS/MODBUS RTU with built-in BOP protection: IP20/ UL open size: QB 68x142x128 (WxHxD)
Product Code	5680
Comparative Metals Coefficient	05.07.2010
Unit of Measure	ST
Product ID	6SL3210-5BB17-5UV1
AL Field	N
Customs Tariff Code	85044095
Compliance	Produkt zgodny z RoHS od: 05.07.2010
Configurable Product	False
Country of Origin	CN
EAN	4042948669860.0
ECCN	N
eClass 6	27-02-31-01
eClass 7.1	27-02-31-01
eClass 8	27-02-31-01