

6SL3210-5BE32-2CV0

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 6sl3210-5be32-2cv0 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Legacy / discontinued |

Technical specification

| | |
|--------------------------------|--------------------------------------|
| Weight | 3.17 kgs |
| Product ID | 6SL3210-5BE32-2CV0 |
| AL Field | N |
| Customs Tariff Code | 85044095 |
| Compliance | Produkt zgodny z RoHS od: 05.07.2010 |
| Configurable Product | False |
| Country of Origin | CN |
| EAN | 6940408103092.0 |
| ECCN | N |
| eClass 6 | 27-02-31-01 |
| eClass 7.1 | 27-02-31-01 |
| eClass 8 | 27-02-31-01 |
| eClass Version 9 | 27-02-31-01 |
| eClass Version 9.1 | 27-02-31-01 |
| ETIM 7 | EC001857 |
| Group Classification Key | R220 |
| List of Characteristics | SINAMICS V20 |
| Quantity in Package | 1 |
| Packaging Length | 209,00 |
| Packaging Width | 243,50 |
| Packaging Height | 264,50 |
| Packaging Size | MM |
| Product Code | 5681 |
| Comparative Metals Coefficient | 05.07.2010 |
| Unit of Measure | ST |
| UPC | 887621902001.0 |

Description

SINAMICS V20 380-480 V 3AC -15%/+10% 47-6 Rated power 22 kW with 150% overload for 60 sec. small output overload: 30 kW with 110% overload for 60 sec. Integrated filter C3 I/O interface: 4 DI, 2 DQ, 2 AI, 1 AO Fieldbus: USS/Modbus RTU with built-in BOP Degree of protection IP20/UL open Size: Size E 244x265x209 (W)