

### 6SL3210-5FB10-1UF2

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6sl3210-5fb10-1uf2
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	1.36 kgs
<b>Product ID</b>	6SL3210-5FB10-1UF2
<b>AL Field</b>	N
<b>Customs Tariff Code</b>	85044095
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.04.2013
<b>Configurable Product</b>	False
<b>Country of Origin</b>	CN
<b>EAN</b>	4042948692776.0
<b>ECCN</b>	N
<b>eClass 6</b>	27-02-31-01
<b>eClass 7.1</b>	27-02-31-01
<b>eClass 8</b>	27-02-31-01
<b>eClass Version 9</b>	27-02-31-01
<b>eClass Version 9.1</b>	27-02-31-01
<b>ETIM 7</b>	EC001857
<b>Group Classification Key</b>	R220
<b>List of Characteristics</b>	SINAMICS V90
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	217,00
<b>Packaging Width</b>	77,00
<b>Packaging Height</b>	237,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	SINAMICS V90, with PROFINET Input voltage: 200-240 V 1/3-phase AC -15%/+10% 2.5/1.5 A 45-66 Output voltage: 0 – Input voltage: 1.2 A 0-330 Hz Motor: 0.1 kW Degree of protection: IP20 Size A, 45x170x170 (WxHxD)
<b>Product Code</b>	4R31
<b>Comparative Metals Coefficient</b>	01.04.2013
<b>REACH</b>	Lead CAS-Nr. 7439-92-1
<b>Unit of Measure</b>	ST