

6SL32101PC222AL0

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 6sl32101pc222al0 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Legacy / discontinued |

Technical specification

| | |
|--------------------------------|--------------------------------------|
| ECCN | N |
| eClass 6 | 27-02-31-01 |
| eClass 7.1 | 27-02-31-01 |
| eClass 8 | 27-02-31-01 |
| eClass Version 9 | 27-02-31-01 |
| eClass Version 9.1 | 27-02-31-01 |
| ETIM 7 | EC001857 |
| Group Classification Key | R220 |
| List of Characteristics | D11.1SD |
| Quantity in Package | 1 |
| Packaging Length | 185,00 |
| Packaging Width | 157,00 |
| Packaging Height | 440,00 |
| Packaging Size | MM |
| Product Code | 9772 |
| Comparative Metals Coefficient | 01.07.2006 |
| REACH | Lead CAS-Nr. 7439-92-1 |
| Unit of Measure | ST |
| Product ID | 6SL3210-1PC22-2AL0 |
| AL Field | N |
| Customs Tariff Code | 85044095 |
| Compliance | Produkt zgodny z RoHS od: 01.07.2006 |
| Configurable Product | False |
| Country of Origin | GB |
| EAN | 4042948666371.0 |
| UPC | 887621831011.0 |
| Weight | 5300 |

Description

SINAMICS POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER
3AC200-240V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 4KW FOR 200% 3S,150% 57S,100% 240S
AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 5,5KW FOR 150% 3S,110% 57S,100% 240S
AMBIENT TEMP -10 TO +40 DEG C 355 X 140 X 165 (HXWXD), FSC PROTECTION IP20 WITHOUT
CONTROL UNIT AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.6